



SUMMARY INFORMATION:

- LASER MARKING MACHINE ON PROMOTION, HIGH COST PERFORMANCE.
 FIBER LASER GENERATOR, LOW CONSUMPTION, EASY FOR MAINTAIN.
 MACHINE SIZE,32CMx66CMx69CM.CASE SIZE,45CMx27CMx41CM.
 OPTIONAL LENS FOR DIFFERENT MARKING AREA

APPLICATION:

- 1.VARIOUS METAL MATERIALS, PART OF NON-METAL MATERIALS.

 2.THE FIBER OPTIC LASER OSCILLATOR MARKER HAS ADVANTAGE OF HIGH BEAM QUALITY AND HIGH RELIABILITY. IT IS SUITABLE FOR PROCESSING FIELDS THAT NEED HIGH MARKING DEPTH, SMOOTHNESS AND ACCURACY.
- ELECTRONIC COMPONENTS INDUSTRY
 IC CARD INDUSTRY
 PLASTIC TOOL INDUSTRY

- MEDICAL DEVICE INDUSTRY
 GLASSES, WATCH AND CLOCK
 KITCHEN AND BATHROOM APPLIANCE

| SPECIFICATION: | |
|--------------------------|---|
| MACHINE MODEL | ZCGX-DS |
| LASER | RAYCUS |
| WAVELENGTH LENS | F-THETA WAVELENGTH LENS |
| SOFTWARE | EZCAD |
| BOARD | BEIJING JCZ MAIN BOARD |
| GALVO | SINO-GALVO SCANNER HEAD |
| LASER WAVELENGTH | 1064NM |
| LASER POWER | 20W 30W 50W FOR CHOICE |
| REPETITION FREQUENCY | 0-100KHZ |
| MINIMUM LINE WIDTH | 0.012MM |
| MARKING RANGE | 100MM*100MM-300MM*300MM |
| MARKING DEPTH | ≤0.4MM(BY MATERIALS) |
| MARKING SPEED | ≤1000MM/S |
| REPEATABILITY | ±0.001MM |
| POWER SUPPLY REQUIREMENT | 110V/220V/SINGLE-PHASE/50HZ/3A |
| TOTAL POWER | 500W (POVER SAVING) |
| COOLING METHOD | BUILT IN AIR COOLING |
| FILE FORMAT | ALL FONT/FONT OF WINDOWS OPERATING SYSTEM FONT LIBRARY |
| OPERATING SYSTEM | WINDOWS LATEST SYSTEM/XP/2000/ 98 SYSTEM |
| COMPUTER | YES |
| RED LASER TARGET | YES |

PRODUCT SIZE








MACHINE SIZE LENGTH: 32CM WIDTH: 66CM HEIGHT: 69CM

CONFIGURATION PRESENTATION:



RAYCUS LASER SOURCE





FIELD LENS



EZCAD SOFTWARE







SINO-GALVO

SAMPLES:



TOOL









HANGTAG





METAL BRACELET

SMALL PENDANT

SMALL ORNAMENT